


LMR BATTERY SPECIFICATIONS	PART NUMBER
	C4493LIPIC

COMPATIBLE RADIOS	Motorola APX900, APX1000, APX2000, APX3000, APX4000, XPR3300, XPR3300e, XPR3500, XPR3500e, XPR7350, XPR7350e, XPR7550, XPR7550e, XPR7580, XPR7580e, DP4400, DP4401, DP4600, DP4601, DP4800, DP4801
REPLACES OEM BATTERY	PMNN4493, PMNN4493A
COMPATIBLE CHARGERS	Endura EC1-MT16B, EC1M-MT16B, EC2M-MT16A-D, EC6M-MT16B, EC12M-MT16A-D / Logic LEVCA-MT16 / Motorola IMPRES WPLN4222, PMPN4284
VOLTAGE	7.4V
CAPACITY	3500 mAh / 25.9 Wh
CHEMISTRY / CELL TYPE	LiPo / AET 501-753898-3400
BATTERY TYPE	Smart
OPERATING TEMPERATURE	-20° C to +55° C (discharge) / 20° C to +45° C (charge)
CHARGE CYCLES	>400
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Smart battery calibrates on Motorola IMPRES 1 and 2 chargers
PROTECTION TYPES	Short circuit / over-charge / over-discharge / over-temperature monitoring via charge contact
HOUSING MATERIAL / SEAL	ABS / ultrasonic weld
INGRESS PROTECTION	IP67 rated
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	Included (CL7144)
WARRANTY	12 months
<p>Our Newest Highest Power APX1000 / XPR3300 Battery</p> <p>The Industry Leader</p>	 <div style="border: 1px dashed black; padding: 5px; margin-left: auto; margin-right: auto;"> <p>Dimensions (HxWxD): 4.51" x 2.18" x 0.91" 114.5 mm x 55.4 mm x 23.1 mm).</p> </div>