

Motorola APX6000 In-Vehicle Charger

Rugged Single Unit Charger

EVC-MT19



For APX6000, APX6000XE, APX8000, APX8000XE, SRX2200 radios
(available special order for APX7000, APX700XE).



- Tested to 9 g-force and NFPA compliant.
- Radio may stay powered on while charging.
- Properly charges OEM batteries with higher end voltage requirements, including PMNN4485, PMNN4486, PMNN4504, and PMNN4494.
- Includes DC hardwire cable and easy release tie-down strap.
- USB port for charging mobile phones or tablets.
- AMPS pattern with optional dash / floor mounting brackets available.

Housing Materials	ABS / PC blend with metal support frame
Contact Type	Custom design probe contact for fail-safe battery connection
Operating Temperature	0° C to 45° C / 32° F to 113° F
Charge Rate (Radio Battery)	800 mA
Compatible Chemistries	Li-Ion / LiPo / NiMH
Input Voltage (Minimum)	12V / 2.8A for charging device from USB port and radio battery
USB Charging Port	For Type A connector / 5V output / 2A charge rate
DC Power Cable (EVC-HW)	Included with EVC-MT19, 16AWG / 3m (9.8') length / secure 4-pin connector
Unit Dimensions (W x H x D)	2.6" x 5.3" x 3.1" / 66.4 x 133.9 x 77.8 mm
Unit Weight	0.60 lbs. / 272 g

LEVCA-M



LEVCA-MHD



Innovative Solutions for Public Safety Professionals



EVC-MT19-4
Rugged 4-unit model also available.