

C234361LI-33

www.criticalbattery.com

SPECIFICATION	DETAILS
COMPATIBLE RADIOS	L3Harris P5300, P5350, P5370, P5400, P5450, P5470, P5500, P5550, P5570, P7300, P7350, P7370, XG-15P, XG-25P, XG-75P, XL-45P, XL-95P
REPLACES OEM BATTERY	L3Harris BT-023436-001
COMPATIBLE CHARGERS	Endura EC1-HA1A, EC1M-HA1A, EC6M-HA1A, EC2M-HA1A-D, EC12M-HA1A-D / L3Harris CH-104560-007, 12082-0314-01
ELECTRICAL RATING	7.2V / 3300 mAh / 24.4 Wh
CHEMISTRY / CELL	Li-Ion / Panasonic NCR18650GA cells or equivalent
CHARGE TYPE	Rapid
CHARGE CYCLES	>500 charge cycles
CONDITIONER COMPATIBLE	Yes (not required for battery run time or cycle life)
OPERATING TEMPERATURE	-20°C to +60°C (discharge) / 10°C to +45°C (charge)
STORAGE TEMPERATURE	-20°C to +50°C
INGRESS PROTECTION	IP64 rated: Fully protected against dust ingress and resistant to water splashes from any direction (suitable for rain and incidental water exposure, but not waterproof and should not be submerged)
HAZLOC LOCATION	Not applicable
WARRANTY	18-month extended warranty for capacity (80%), materials, & workmanship
FEATURES	Short-circuit, over-charge, over-discharge, and over-temperature protection
DIMENSIONS (HxWxD)	4.52" x 2.44" x 1.01" (114.8 x 62.0 x 25.7 mm)
WEIGHT	0.379 lb (171.63 g)
HOUSING CONSTRUCTION	ABS housing with ultrasonic-welded seal
INTERNAL CONSTRUCTION	Pure nickel tabs with spot-welded construction and corrosion-resistant gold-plated contacts
BELT CLIP	Includes belt clip (part number CL234065HT)
COMPATIBLE CARRY SOLUTIONS	None identified

Sandown Wireless
 19 Phillipswood road
 Sandown, NH 03873
 email: sales@criticalbattery.com
 Office: 603-425-9876
 web: www.criticalbattery.com

