

LE234066LIIS

www.criticalbattery.com

SPECIFICATION	DETAILS
COMPATIBLE RADIOS	L3Harris P5300, P5350, P5370, P5400, P5450, P5470, P5500, P5550, P5570, P7300, P7350, P7370, XG-15P, XG-75P, XG-25P, XL-95P
REPLACES OEM BATTERY	Harris BT-023406-006 (2000 mAh)
COMPATIBLE CHARGERS	Endura EC1-HA1A, EC1M-HA1A, EC6M-HA1A, EC2M-HA1A-D, EC12M-HA1A-D / EVC-HA3, EVC-HA3-4 / Harris CH-104560-007, CH-104570-016
ELECTRICAL RATING	7.4V / 2500 mAh / 18.5 Wh
CHEMISTRY / CELL	Li-Ion / Panasonic UR18650ZY cells
CHARGE TYPE	Rapid
CHARGE CYCLES	>400 charge cycles
CONDITIONER COMPATIBLE	Not applicable
OPERATING TEMPERATURE	-20° C to +60° C (discharge) / 0° C to +45° C (charge)
STORAGE TEMPERATURE	1 year: -20°C to +20°C; 3 months: -20°C to +40°C; 1 month: -20°C to +50°C
INGRESS PROTECTION	IP64 rated: Fully protected against dust ingress and resistant to water splashes from any direction (suitable for rain and incidental water exposure, but not waterproof and should not be submerged)
HAZLOC LOCATION	Certified by SGS to TIA-4950 / CSA C22.2 No. 157 / UL 913 5th Edition standard for intrinsically safe use (Division 1 / Classes 1, 2, 3 and Groups A, B, C, D, E, F, G / Class T4) and non-incendive use (Division 2, Classes 1, 2, 3 and Groups A, B, C, D, E, F, G / Class T4)
WARRANTY	18-month extended warranty for capacity (80%), materials, & workmanship
FEATURES	Short-circuit, over-charge, over-discharge, and over-temperature protection
DIMENSIONS (HxWxD)	4.53" x 2.44" x 1.02" (115 x 62 x 26 mm)
WEIGHT	0.366 lbs (165.77 g)
HOUSING CONSTRUCTION	ABS housing with ultrasonic-welded seal
INTERNAL CONSTRUCTION	Pure nickel tabs with spot-welded construction and corrosion-resistant gold-plated contacts
BELT CLIP	Not applicable
COMPATIBLE CARRY SOLUTIONS	None identified



Sandown Wireless
 19 phillipswood Road
 Sandown, NH 03873
 Office: 603-425-9876
 email: sales@criticalbattery.com